CARRYALL 4X4 SERIES

Club Car

UNSURPASSED DURABILITY, WORRY-FREE PERFORMANCE

You want a vehicle you can depend on, one that won't get stuck in the mud or fall behind. With auto-locking differentials, aircraft-grade frames, and 4-link, semiindependent rear suspension, our 4WD vehicles are ready to handle whatever you throw at them.

CARRYALL 1700

www.clubcarsa.co.za | info@afgriequipment.co.za







CARRYALL 1500 MUSCLE MEETS FLEXIBILITY

IntelliTrak™ automatically senses the terrain and shifts power for maximum traction. Combined with a 2000-pound towing capacity and automotive-style rear suspension, the Carryall 1500 can handle any job.



Horsepower 20 hp (gasoline) 20 hp (diesel)

CARRYALL 1500 Intellitach

OUR MOST VERSATILE UTV

The same automatic 4WD system as our Carryall 1500 plus exclusive IntelliTach™ quick-change hydraulic tool attachment system. It's a mini forklift to help you do your best work.



Horsepower 20 hp (diesel)

CARRYALL 1700 SEATS FOUR AND HAULS CARGO

With automatic four-wheel drive, four seats, and a full-size truck bed, Carryall 1700 can haul more cargo and passengers to places others fear to tread.



Max Vehicle Capacity



Horsepower 20 hp (gasoline) 20 hp (diesel)

READY FOR A HARD DAY'S WORK Our new 4x4 Passenger Cab features 40% more airflow and a variety of accessories for comfort, efficiency, and versatility. Carryall AWD UTVs with an added cab help you get a variety of jobs done, even on tough terrain or in extreme weather conditions. 1030 Ngi Capatiy E



Intellatach **KEEP YOUR** ESSENTIALS READY

Reduce the need for expensive construction equipment and get a variety of jobs done quickly with our exclusive IntelliTach™ quick-change tool attachment system.





Front Bucket

Pallet Forks




Plow Blade













High Capacity Updgrade

OPTIONS & ACCESSORIES

Ask your Club Car sales representative for details.









Strobe Light







CARRYALL 1500



Club Car









	GASOLINE	DIESEL	DIESEL W/ INTELLITACH	GASOLINE	DIESEL
ENGINE	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade	Kubota D722, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade
HORSEPOWER	20.1 hp (15 kW) rated @ 3400 RPM per SAE J1349	20 hp (15 kW) rated © 3600 RPM per SAE J1995	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	20.1 hp (15 kW) rated © 3400 RPM per SAE J1349	20 hp (15 kW) rated @ 3600 RPM per SAE J1995
BATTERIES	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve
STEERING	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering
FRONT SUSPENSION	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks
REAR SUSPENSION	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle
BRAKES	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc	Twin piston front, single piston rear hydraulic disc
PARK BRAKE	Mechanical disc	Mechanical disc	Mechanical disc	Mechanical disc	Mechanical disc
TIRES	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply
BED LXWXH	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)
WHEELBASE	82 in (208 cm)	82 in (208 cm)	82 in (208 cm)	114 in (290 cm)	114 in (290 cm)
GROUND CLEARANCE	8.2 in (21 cm)	8.2 in (21 cm)	7.3 in (19 cm) - under differential 11.1 in (28 cm) - under floorboard	8.2 in (21 cm)	8.2 in (21 cm)
FUEL TANK CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)
CURB WEIGHT	1430 lb (649 kg)	1550 lb (703 kg)	1751 lb (794 kg)	1630 lb (739 kg)	1750 lb (794 kg)
BED CAPACITY	Standard 800 lb (363 kg); With HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg); With HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg)	800 lb (363 kg)	800 lb (363 kg)
PAYLOAD CAPACITY	Standard 1200 lb (544 kg); With HD Suspension 1450 lb (658 kg)	Standard 1200 lb (544 kg); With HD Suspension 1450 lb (658 kg)	Standard 1200 lb (544 kg)	1600 lb (726 kg)	1600 lb (726 kg)
TOWING CAPACITY	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)
OVERALL HEIGHT	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)
OVERALL LENGTH	124.6 in (317 cm)	124.6 in (317 cm)	121 in (307 cm) - w/o attachment arm and w/ cylinders stored 136 in (345 cm) - w/ attachment arm and cylinder fully extended 155 in (394 cm) - max extended position	154 in (391 cm)	154 in (391 cm)
OVERALL WIDTH	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)
SPEED RANGE	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)
LIMITED WARRANTY	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty